# HX SEALED SERIES for HYBRID

## 4.8mm (187)

(E) (J)
Cable size : 適用電線サイズ
Cable overall diameter : 電線仕上り外径
Heat-resistant copper alloy : 耐熱銅合金

Brass : 黄銅 Surface treatment : 表面処理 Gold-plated : Auメッキ Tin-plated : Snメッキ

## Terminal (UNIT: mm)

## Ref; 4.8mm Terminal detail


**S M(8100-0463**) B-21 **M M(8100-0464**) B-22

**L** M(8100-0465) B-22 F(8100-0468) B-22


# 4.8mm (187)

# Wire seals (UNIT: mm)

The wire seals are common to M and F. ワイヤシールは M、F 共用です。




( <b>M</b> )		
		F (8100-0660)
Cable size (mm²)	0.5~1.25	3.8
Cable overall diameter(mm)	1.6~2.6	6
Material	Heat-resistant copper alloy	19.5
Surface treatment	Tin-plated	




( <b>M</b> )		
		(7165-0130)
Cable size (mm²)	(AV/0.5~1.25) (AVX/0.5~1.25) (AVS/0.3~1.25) (AVSS/0.85~2.0) (AVSSX/0.75~2.0)	\$8
Cable overall diameter(mm)	1.8~2.9	
Material	NBR	
Color	Gray	9

### (7165-0131) (AV/2.0~3.0) (AVX/2.0~3.0) Cable size (mm²) (AVS/2.0~3.0) Cable overall diameter(mm) 3.0~4.1 Material NBR Color Black


(M)		
		(7165-0147)
Cable size (mm²)	(AVS/0.3~1.25)	<i>\\phi</i> 8
Cable overall diameter(mm)	1.8~2.9	
Material	Silicone	
Color	Dark Green	9
















M (6181-6921)

F (6189-7567)




Color Dark gray

# 2.3mm, 4.8mm (090, 187)

# Housing (UNIT:mm)

Ref: Terminal part No.	[2.3mm] [4.8mm]	E-17 E-20
Ref: wire seal No.	[2.3mm] [4.8mm]	E-18 E-20
Ref: Dummy plug No.	[2.3mm] [4.8mm]	J-07 B-23
Material	PBT	

No. of way/ ( ) corresponds to 2.3mm, 4.8mm, in order from left to right. 極数/( ) 内表示: 左から2.3mm 極数、4.8mm 極数



E-22