



注記

- 1) 嵌合相手品番: 7122-6043-30
- 2) 適用端子品番: 7116-2870, 7116-2871, 7116-2872
- 3) 適用リヤホルダ品番: 7157-6241-40

NOTES

- 1) MATING PART NO.: 7122-6043-30
- 2) APPLICABLE TERMINAL NO.: 7116-2870, 7116-2871, 7116-2872
- 3) APPLICABLE REAR HOLDER NO.: 7157-6241-40

ISSUE MARK

GENERAL TOLERANCE							
	10MAX	50MAX	100MAX	250MAX	2500VR	ANGLE	ECCENT
A	±0.15	±0.2	±0.3	±0.5	±0.75	±30'	0.1
B	±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1
◎	±0.3	±0.5	±0.8	±1.4	±2	±30'	0.15

CUSTOMER		MATERIAL		TREAT.	
CUSTOMER PART NO.		SPEC.		NYLON (BLACK) & FIN.	
OFFICE		NAME		M TYPE CONNECTOR	
VENDOR		STD LIB NO.		HOUSING 4PF(B)	
VENDOR NO.		DWG SOURCE		PART NO. 7123-6043-30	
DWG TYPE		DWG DATE		UNIT	
R		NEW		88.10.14 mm	
APPROVED		CHECKED		DESIGN	
K. Saito		M. Maeda		DRAWN	
88.12.12		88.12.09		SAKAI S. YAGI	
WEIGHT		DWG NO.		TRIAL PART NO.	
g		7123-6043-30R			
		82.08.08		88.10.14	
		YAZAKI CORPORATION			

88.12.08	NEW	8MC-3158	T.M
LET	DATE	REVISION RECORD	NO. CHKD