注 記

1. 適用電線サイズ : CAVUS 0.85~1.25 △2
   : CAVS 0.3~0.85 △2
   : AVS 0.3 △2
2. 材料は含油シリコンゴム (緑)
3. 適用端子品番 : 7114-1232, 7116-1236
   7116-1232, 7116-1246

NOTES

1. APPLICABLE WIRE SIZE : CAVUS 0.85~1.25 △2
   : CAVS 0.3~0.85 △2
   : AVS 0.3 △2
2. MATERIAL : SELF-LUBRICATION SILICONE RUBBER (GREEN)
3. APPLICABLE TERMINAL PART NO. : 7114-1232, 7116-1236
   7116-1232, 7116-1246

RUBBER PART GENERAL TOLERANCE

PART DIM.	1	2	③
0 TO 3	± 0.2	± 0.3	± 0.4
3 TO 6	± 0.2	± 0.4	± 0.5
6 TO 10	± 0.3	± 0.5	± 0.6
10 TO 18	± 0.3	± 0.6	± 0.8
18 TO 30	± 0.4	± 0.8	± 1.0
30 TO 50	± 0.5	± 1.0	± 1.5
50 TO 80	± 0.6	± 1.2	± 2.0
80 TO 120	± 0.7	± 1.4	± 2.5
120 TO 180	± 0.8	± 1.6	± 3.0
180 TO 250	± 1.0	± 2.0	± 4.0
250 TO 315	± 1.2	± 2.5	± 5.0
315 TO 400	± 1.5	± 3.0	± 6.0
400 TO 500	± 1.8	± 3.5	± 7.0
500 OVER	± 0.4 %	± 0.8 %	± 1.5 %





ISSUE MARK

LET	DATE	REVISION RECORD	NO.	CHKD
△3	06/06/28	CHANGED FORM	C06-Z727	M. A
△2	93/12/08	CHANGED APPLICABLE WIRE SIZE	C93-7153	M. K
△1	91/05/06	RENEW	C91-L183	M. K

GENERAL TOLERANCE

	10MAX	50MAX	100MAX	250MAX	2500VR	ANGLE	ECCENT
A	±0.15	±0.2	±0.3	±0.5	±0.75	±30′	0.1
B	±0.2	±0.3	±0.55	±0.95	±1.4	±30′	0.1
C	±0.3	±0.5	±0.8	±1.4	±2	±30′	0.15

SPECIFIED VDI2005

MASS g

CUSTOMER
CUSTOMER PART NO. | CUSTOMER DWG NO.
OFFICE | TRIAL PART NO.
VENDOR
VENDOR NO.

DWG TYPE	DWG SOURCE	DWG DATE	UNIT	SCL	ANGLE
R	RENEW	91/05/06	mm	5:1	3

APPROVED	CHECKED	CHECKED	DESIGN	DRAWN
移山	市堀	秋山	SAKAI	C. REPOLLO
06. 6. 29	06.06.29	06/06/29	85/01/16	06/06/28

MATL. SPEC. SEE NOTES | TREAT. & FIN.

NAME W TYPE SEAL RUBBER (FOR THIN WIRE)

PART NO. CH. CODE 7157-3563-60

DWG NO. 7157-3563-60:R | SET DWG NO.

YAZAKI CORPORATION