



TABLE 1  
△

SUB ASSEMBLY PART NO. AND CH. CODE	NO.	PART NO. AND CH. CODE	MATERIAL	COLOR	△ QTY.
7283-1065 ETC.	①	SEE TABLE 2	△ HPA	SEE TABLE 2	1
	②	7157-4042 △(7B57-4042)	△ HPA	△ NATURAL	1

△ TABLE 2

SUB ASSEMBLY PART NO. AND CH. CODE	PART NO. AND CH. CODE	COLOR
7283-1065. △ △(7C83-1065)	7183-1065 △(7B83-1065)	NATURAL
7283-1065-10. △	7183-1065-10	DARK GRAY
7283-1065-30. △	7183-1065-30	BLACK
7283-1065-40. △	7183-1065-40	LIGHT GRAY
7283-1065-90. △	7183-1065-90	BLUE

注記

1. 嵌合相手品番: 7282-1065 ETC.
2. 適用端子品番: 7116-4030 ETC.
- △ 3. ( ) 内品番は、A/B回路及び特別管理回路に使用すること。

NOTES

1. MATING PART NO. : 7282-1065 ETC.
2. APPLICABLE TERMINAL NO. : 7116-4030 ETC.
- △ 3. PART NUMBERS IN PARENTHESIS SHALL BE USED FOR AIR BAG (A/B) CIRCUITS AND OTHER CIRCUITS DESIGNATED FOR SPECIAL MONITOR.

△	00.05.15	CORRECT ALL ERROR	C00-L735	H. T									
△	98.12.23	ELIMINATED COLOR NO.	C98-N181	T. M									
△	98.11.04	CHANGED FORM. MATERIAL & ADDED PART NO. . NOTES. △	C98-M887	T. M									
△	90.11.10	CHANGED SPACER COLOR	C90-M205	M. H									
	89.07.19	NEW	C89-L350	H. I									
LET	DATE	REVISION RECORD	NO.	CHKD									
GENERAL TOLERANCE													
	10MAX	50MAX	100MAX	250MAX	2500VR	ANGLE	ECCENT	DWG TYPE	DWG SOURCE	DWG DATE	UNIT	SCL	ANGLE
A	±0.15	±0.2	±0.3	±0.5	±0.75	±30'	0.1	R	NEW	89.07.19	mm	2/1	3
B	±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	APPROVED	CHECKED	CHECKED	DESIGN	DRAWN	
(C)	±0.3	±0.5	±0.8	±1.4	±2	±30'	0.15				Y. OHTA	MIYAJIMA	
SPECIFIED					MASS			加藤	川梨	鈴木(正)			
					g			00.05.19	00.05.18	00.05.18	88.11.30	00.05.15	

CUSTOMER		MATL. SPEC.		TREAT. & FIN.	
CUSTOMER PART NO.		CUSTOMER DWG NO.		SEE TABLE 1	
OFFICE		TRIAL PART NO.		NAME	
VENDOR		VENDOR NO.		187 6P CONNECTOR	
GENERAL TOLERANCE		PART NO. CH. CODE		SUB ASSEMBLY FEMALE	
10MAX		7283-1065 ETC. △(7C83-1065)			
50MAX		DWG NO.		7283-1065:R	
100MAX		SET DWG NO.			
250MAX		YAZAKI CORPORATION			
2500VR					
ANGLE					
ECCENT					
DWG TYPE					
DWG SOURCE					
DWG DATE					
UNIT					
SCL					
ANGLE					

ISSUE MARK